

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

• **Trade name:** GEAR OIL HD 80W90

• **Article number:** A518

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** ·

#### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

• **Product category** PC24 Lubricants, greases, release products ·

#### Process category

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC8a Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at dedicated facilities

PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems ·

#### Environmental release category

ERC9a Wide dispersive indoor use of substances in closed systems

ERC9b Wide dispersive outdoor use of substances in closed systems ·

**Application of the substance / the mixture** Lubricating oil

• **1.3 Details of the supplier of the safety data sheet** ·

#### Manufacturer/Supplier:

Arvina Lubricants BV  
Caumerbeeklaan 54  
6416 GA Heerlen  
info@arvina-lubricants.com  
0031(0)458801066

• **Further information obtainable from:** Product safety department - 0031(0)458801066.

• **1.4 Emergency telephone number:** 0031(0)458801066 (9 AM to 4 PM, Monday to Friday)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

• **Classification according to Regulation (EC) No 1272/2008**

The product is not classified according to the CLP regulation.

• **Classification according to Directive 67/548/EEC or Directive 1999/45/EC** Not applicable.

• **Information concerning particular hazards for human and environment:**

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 2.2 Label elements

• **Labelling according to Regulation (EC) No 1272/2008** Void ·

**Hazard pictograms** Void

• **Signal word** Void

• **Hazard statements** Void

• **Additional information:**

EUH208 Contains Polysulfides, di-tert-Bu, Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched). May produce an allergic reaction.

EUH210 Safety data sheet available on request. ·

### 2.3 Other hazards

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

Trade name: GEAR OIL HD 80W90

(Contd. of page 1)

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · **Dangerous components:**

CAS: 68937-96-2 EINECS: 273-103-3 Reg.nr.: 01-2119540515-43	Polysulfides, di-tert-Bu ☒ Xi R38; ☒ Xi R43 R52/53	2.5-10%
	☠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	
	Interchangeable low viscosity base oil (<20,5 cSt @40 °C) *	1-2.5%
	☠ Asp. Tox. 1, H304	
EC number: 931-384-6 Reg.nr.: 01-2119493620-38	Reaction products of bis(4-methylpentan-2-yl) 1,2-dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	1-2.5%
	☒ Xn R22; ☒ Xi R41; ☒ Xi R43; ☒ N R51/53	
	☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411; ☠ Acute Tox. 4, H302; Skin Sens. 1, H317	

#### · **Additional information:**

\* Contains one or more of the following CAS-numbers: 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-65-0, 64742-71-8, 68037-01-4, 72623-83-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 8042-47-5, 848301-69-9.

For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

· **General information:** No special measures required.· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** Generally the product does not irritate the skin.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** Do not induce vomiting; call for medical help immediately.

### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed if swallowed or in case of vomiting, danger of entering the lungs.**

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

#### · **Suitable extinguishing agents:**

CO<sub>2</sub>, dry chemical, or foam. Water can be used to cool and protect exposed material. ·

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

### · 5.3 Advice for firefighters

#### · **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

GB

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

Trade name: GEAR OIL HD 80W90

(Contd. of page 2)

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

### · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. ·

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Remove from the water surface (e.g. skim or suck off).

### · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

No special measures required.

Avoid the formation of oil haze.

### · Information about fire - and explosion protection: No special measures required.

### · 7.2 Conditions for safe storage, including any incompatibilities ·

#### Storage:

#### · Requirements to be met by storerooms and receptacles: Store only in the original receptacle. ·

Information about storage in one common storage facility: Not required.

#### · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

### · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · Additional information about design of technical facilities: No further data; see item 7. ·

### 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

#### · Additional information: The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures: Wash hands before breaks and at the end of work. ·

Respiratory protection: Not required.

#### · Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves

#### · Material of gloves

Nitrile rubber, NBR

PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

**Trade name: GEAR OIL HD 80W90**

(Contd. of page 3)

• **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Goggles recommended during refilling •

**Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties •**

**General Information**

• **Appearance:**

<b>Form:</b>	Liquid
<b>Colour:</b>	Brown
<b>Odour:</b>	Characteristic

• **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.

• **Drip point:**

<b>Pour point</b>	-30 °C (ASTM D97)
-------------------	-------------------

• **Flash point:**

> 110 °C

• **Flammability (solid, gaseous):**

Not applicable.

• **Ignition temperature:**

200 °C

• **Self-igniting:**

Product is not selfigniting.

• **Danger of explosion:**

Product does not present an explosion hazard.

• **Explosion limits:**

<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	7.0 Vol %

• **Density at 20 °C:**

0.892 g/cm<sup>3</sup>

• **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

• **Partition coefficient (n-octanol/water):** Not determined.

• **Viscosity:**

40 °C

149 mm<sup>2</sup>/s (ASTM D445)

• **Solvent content:**

**Organic solvents:** 0.0 %

• **9.2 Other information**

No further relevant information available.

## SECTION 10: Stability and reactivity

• **10.1 Reactivity**

• **10.2 Chemical stability**

• **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.

• **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents. •

**10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

Trade name: GEAR OIL HD 80W90

(Contd. of page 4)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**  
The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.  
When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.
- **Sensitisation**  
For skin sensitisation: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.  
For respiratory sensitisation: Not expected to be a sensitizer.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is difficultly biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**  
This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

Trade name: GEAR OIL HD 80W90

(Contd. of page 5)

- **European waste catalogue**

13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
-----------	---

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, ADN, IMDG, IATA** Void

- **14.2 UN proper shipping name**

- **ADR, ADN, IMDG, IATA** Void

- **14.3 Transport hazard class(es)**

- **ADR, ADN, IMDG, IATA**

- **Class** Void

- **14.4 Packing group**

- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:**

- **Marine pollutant:** No

- **14.6 Special precautions for user**

Not applicable.

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **UN "Model Regulation":**

-

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **National regulations:**

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

R22 Harmful if swallowed.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

(Contd. on page 7)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 08.01.2015

Version number 1

Revision: 07.01.2015

**Trade name: GEAR OIL HD 80W90**

(Contd. of page 6)

R51/53 Toxic to aquatic organisms , may cause long -term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms , may cause long -term adverse effects in the aquatic environment.

· **Department issuing MSDS:** Product safety department. ·

**Contact:** Product safety department

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin

Sens. 1: Sensitisation - Skin, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **Sources**

67/548/EEC

99/45/EEC

EC/453-2010

GB