

ARVIMATIC S41

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

ARVIMATIC S-41 meets the following specifications

GM DEXRON VI
VOITH: H55.6335xx
AML: 4G4319A509/AA/S
BENTLEY: PY112995PA
BMW: 83220142516 BMW: 83222152426
BMW: M-1375.4 (8322 0142516)
HYUNDAI: 040000C90SG
JAGUAR: Fluid 8432 JAGUAR: 02JDE26444
LAND ROVER: TYK500050, LR023288
MASERATI: 231603
MB 236.14, MB 236.12, MB 236.41
AISIN-WARNER: AW-1
AISIN-WARNER: JWS 3324
CHRYSLER: 68157995AA
FIAT: 9.55550-AV2
FIAT: 9.55550-AV5
FORD: MERCON LV
FORD: MERCON SP
FORD: WSS-M2C924-A
HONDA: DW-1
HYUNDAI: NWS-9638 T5
HYUNDAI: SPH-IV
HYUNDAI: SP-IV
MAZDA: FZ
MITSUBISHI: ATF J3,
NISSAN: MATIC-S
TOYOTA: AUTO FLUID WS
VW: G 055 005
VW: G 055 162
VW: G 055 540
VW: G 060 162
JWS 3324
SAAB 93 165 147
KIA / HYUNDAI SP-IV/ SPH-IV
ZF: TE-ML 11
ZF Lifeguard Fluid 6 (S671 090 255)
ZF Lifeguard Fluid 8

APPLICATIONS :

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs. Mainly intended for the 6 or 8 speed automatic transmissions from ZF or other manufacturers, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid like Mercedes Benz, Hyundai, Toyota. This transmission oil is very universal in use.

FEATURES :

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : significantly extended transmission life.

Extended oil life : excellent thermal and oxidation stability.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density at 15°C	D4052	g/ml	0,847
Viscosity at 40°C	D445	mm ² /s	29,4
Viscosity at 100°C	D445	mm ² /s	6,1
Viscosity index	D2270		162
Pour point	D6892	°C	-45
Brookfield -40°C	D2983	mPa.s	9500
Flash point COC	D92	°C	210
Colour			AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV555