

GEAR OIL GO 75W80

GEAR OIL MTF 75W80 is a high quality transmission oil, suitable for almost all manual gearboxes of cars. (MTF = MULTI TRANSMISSION FLUID) It is especially suitable as a substitute for specific OEM original oils and simplifies the complexity and storage of gear oils.

GEAR OIL GO 75W80 meets the following specifications:

API GL-4 +

GM 1940182 / GM: 1940768

HONDA MTF 94

MB 235.10

PSA B71 2330 / PSA 9730 A8

FORD ES D-M2C186-A

FORD WSD-M2C200-D

VOLVO 97308

VOLVO 97309

VOLVO 97310

GM 1940768

FIAT 9.55550-MX3

FIAT 9.55550-MZ1

NISSAN MT-XZ

VAG B80 Synchroniser

APPLICATIONS :

Tested under strict conditions, this oil satisfies the general performance requirements of most brands and models, in all weather conditions.

ADVANTAGES :

Improved performance over conventional "Service Fill" oils.

Smooth gear changes and extends the life of the transmission

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE Grade	SAE J306		75W80
Density @15°C	ASTM D4052	kg/m3	877
Kin. Viscosity @40°C	ASTM D7042	mm2/s	50
Kin. Viscosity @100°C	ASTM D7042	mm2/s	9,11
Viscosity Index	ASTM D2270		203
Viscosity Brookfield @-40°C	ASTM D5293	mPa.s	142000
Flash point COC, min	ASTM D92	°C	204
Pour point	ADTM D97	°C	-48

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV511

Arvina lubricants BV Caumerbeeklaan 54 | 6416 GA Heerlen | Tel.: +31(0)45 880 10 66 | info@arvina-lubricants.com
www.arvina-lubricants.com