

GEAR OIL 75W80 V97307

GEAR OIL 75W80 97307 This is a full synthetic lubricant based on carefully selected very high quality base oils, which is recommended for the manual transmissions of most commercial vehicles. It is adapted to the requirements of syncromesh transmissions, procuring improved shift comfort, low temperature fluidity and longer service life

APPLICATIONS:

This product meets the requirements of many commercial vehicle builders and/or gearbox manufacturers, including DAF, IVECO, Eaton Europe (300.000 km or 3 years), Renault (in accordance with B0032/2 Annex 3) and Volvo.

GEAR OIL 75W80 V97307 meets the following performance criteria:

- **MAN: 341 E-3**
- **MAN: 341 Z-4**
- **MB: 235.4**
- **VOLVO: 97305**
- **VOLVO: 97307**
- **ZF: TE-ML 01L-ZF: TE-ML 02L - ZF: TE-ML 08 - ZF: TE-ML 16K**

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE Grade	SAE J306		75W-80
Density @15°C	ASTM D4052	kg/m ³	860
Kin. Viscosity @40°C	ASTM D7042	mm ² /s	57.9
Kin. Viscosity @100°C	ASTM D7042	mm ² /s	9.75
Viscosity Index	ASTM D2270		159
Flash point COC, min	ASTM D92	°C	234
Pour point	ADTM D97	°C	-45

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Product code: ARV510